

■ Brushcutter VB 340



- Forged steel connection rod and crankshaft to guarantee consistently high performance and long life.
- Fitted with generously sized clutch which assures greater control of the machine (cutting tool does not turn on idle), greater engine protection and better performance even on long grass.
- Digital coil with electronic control: assures effortless starting and improves performance, always guaranteeing uniform combustion and low fuel consumption.
- Flywheel with generously sized fins for optimised cooling even at high outside temperatures.
- Primer device draws fuel mixture into the carburettor to facilitate starting with a limited number of pulls, even after long idle periods.
- Supplied as standard, the Tap'n go trimmer head feeds the line out automatically when it touches the ground, without interrupting work.
- Blade in special steel supplied as standard: offers better performance on thick grass or small bushes.
- Self-lubricating sheath protects the transmission and reduces vibration, making work more comfortable.
- Easy access to the filter, without the use of tools, for maximum comfort during maintenance and cleaning.

■ Brushcutter VB 340



TECHNICAL SPECIFICATIONS

Engine	EMAK - 2-stroke
Power / Displacement	1.3 HP - 1.0 kW / 30.5 cm ³
Fuel tank capacity	0.65 L
Transmission / Tube diameter	flexible / 26 mm
Grip	handle
Anti-vibration system	1 on nose cone + self-lubricating sheath + handlebar clamp
Clutch	yes
Weight	6.6 Kg
Standard cutting tools	Tap'n go [®] head Ø 130 mm, Ø 2.4 mm line + disc with 3 teeth Ø 255 mm x 1.8 mm
Cutting diameter	38 cm
Harness	double

PRODUCT DATA

Product Code	61329002E2
Dimensions, single pack (cm)	183 x 27 x 28
Quality / Dimensions, pallet (cm)	40 / 181 x 108 x 128 (24 pcs) 181 x 108 x 88 (16 pcs)
Quality / Truck, 1360 cm	560
Quality / 40' ctr, palletized	480
EAN Code	8026619022723

QUALITY MARKS

